



Carrier Ethernet Release Notes

Date: Feb 24, 2015

Version: 1.9.4

Overview

This release note covers the requirements, important notes, new features and changes, addressed issues and known limitations for the S3280, S3280-TST, S4140, S4212 and S4224 product families.

Management of these products is available using Converge™ EMS, SNMP, Web or Command Line Interface (CLI) locally or via Telnet.

Requirements:

Firmware version 1.9.4 and these release notes apply to the following products:

- S3280
- S3280-TST
- S4140
- S4212
- S4224

New Features and Enhancements:

The following is a list of new features and enhancements for version 1.9.4

- Configurable Banner upon login for Message of the day (MOTD- available via CLI
- 2048 bit https certificate
- Collection of some Performance Monitoring stats on device
- Traps for EPS, ERPS
- Zero Touch Provisioning (ZTP)- ability to be auto discovered by a management system when connected into a network

Known Feature Limitations:

The following is a list of currently known issues for the Carrier Ethernet devices.

- MEPS do not work over ports using link aggregation
- L2CP settings are in the CLI only and not Web interface

Related Documentation:

Please visit the specific product web page for detailed documentation

- Install Guide
- User Guide
- CLI Reference Guide

MIBs:

- tn-mibs-v1.9.4.zip file