



---

## **S3280 Family Release Notes**

**Date: June 19, 2013**

**Version: 1.5.6**

---

### **Overview**

This release note covers the requirements, important notes, new features and changes, addressed issues and known limitations for the S3280 and S3280-TST product families.

Management of the S3280 and S3280-TST is available using Converge™ EMS, SNMP, Web or Command Line Interface (CLI) locally or via Telnet.

### **Requirements:**

Firmware version 1.5.6 and these release notes apply to the following products:

- S3280
- S3280-TST

### **New Features and Enhancements:**

The following is a list of new features and enhancements for version 1.5.6

- Support for RFC 2544 test report (S3280-TST model only)
- Support for Static IP Routing
- New SNMP MIB support added for VCL, LLDP, SAT Loopback, SSH
- New Trap: SOAM

### **Fixes in 1.4.3**

- Minor bug fixes

### **Known Feature Limitations:**

The following is a list of currently known issues for the S3280.

- MEPS do not work over ports using link aggregation
- L2CP settings are in the CLI only and not Web interface

### **Related Documentation:**

- S3280 User Guide (33506)
- S3280 CLI Reference Guide (33507)
- RFC 2544 User Guide (33540)
- Static IP Routing User Guide (33542)

### **MIBs:**

- TNMIBs\_1.5.6.zip file