

S3280 Family Release Notes Date: September 5, 2013 Version: 1.6.4

Overview

This release note covers the requirements, important notes, new features and changes, addressed issues and known limitations for the S3280 and S3280-TST product families.

Management of the S3280 and S3280-TST is available using Converge™ EMS, SNMP, Web or Command Line Interface (CLI) locally or via Telnet.

Requirements:

Firmware version 1.6.4 and these release notes apply to the following products:

- \$3280
- \$3280-TST

New Features and Enhancements:

The following is a list of new features and enhancements for version 1.6.4

- Policer Ordering feature that allows the different policer order options
- New SNMP MIB support added for https

Fixes in 1.6.4

- Fix to allow both options: remote user to use tagged management traffic on fiber port and local user connected to Management port to manage unit with untagged traffic
- DHCP Relay Agent fix for the counter for relay client 'Keep Agent Option'
- Fix for MVR fast leave
- Fix to clear VLAN membership after Factory Default

Known Feature Limitations:

The following is a list of currently known issues for the S3280.

- MEPs do not work over ports using link aggregation
- L2CP settings are in the CLI only and not Web interface

Related Documentation:

- S3280 User Guide (33506)
- S3280 CLI Reference Guide (33507)
- RFC 2544 User Guide (33540)
- Static IP Routing User Guide (33542)

MIBs:

• TNMIBs_1.6.4.zip file