

Transition Networks 10900 Red Circle Drive Minnetonka, MN 55343 www.transition.com

SMxxTAT2SA Release Notes

Date: Nov.20, 2018 Version: 1.02.1363

Overview

This release notes covers firmware version v1.02.1363 for SM8TAT2SA, SM16TAT2SA, SM24AT2SA.

Release Changes and Enhancements

[Enhancements]

- * add SSL certificates
- * Display PoE MCU FW version in the system information page
- * 802.1x supports assign VLAN attribute.
- * DHCP server assign IP addresses based on incoming ports.
- * Add NTP Time Sync Interval.

[Bugs Fixed]

- * Device's http port number can be modified in the topology view, but can't be modified in the DMS device list page.
- * Using API to get PoE "PwrAllocate" value, the value should map to Power Allocated of PoE status.
- * Switch doesn't auto-logout when screen stays idle on the DMS Topology View over 10 minutes.
- * The port doesn't send EAP request to client if the port is not VLAN1 when 802.1 X authentications is enabled
- *Reload factory default; show "Syntax error on line
- * Can't set NTP time sync interval to 5 minutes.
- * Client can't ping the switch when the port is not in the VLAN1 and is passed port-based 802.1X authorized.
- * The PoE interface stops responding to commands after many failures of the PoE Auto Power Reset feature
- * Fix the problem of using % in the password

Known Limitations and Restrictions

N/A