A. Install Python (using FTP):

- 1. If current version of firmware on the PremierWave XN is not 7.9, use the Firmware upgrade procedure mentioned below in section C and then proceed to step 2
- Copy or download the 'premierwave_xn _7_9_0_0RXX_python.rom' or 'premierwave_xn_7_9_0_0RXX+python.rom' to a host computer.
- ftp <IP Address>
 <IP address>: IP address of the PremierWave XN device
 Default login credentials: admin, PASS
- 4. put premierwave_xn_7_9_0_0RXX_python.rom firmware.rom

or,

put premierwave_xn_7_9_0_0RXX+python.rom firmware.rom

The device will automatically reboot after firmware has been updated.

B. Install Python (using web manager):

- 1. If current version of firmware on the PremierWave XN is not 7.9, use the Firmware upgrade procedure mentioned below in section C and then proceed to step 2
- 2. Copy or download the 'premierwave_xn_7_9_0_0RXX_python.rom' or 'premierwave_xn_7_9_0_0RXX+python.rom' to a host computer.
- 3. Using an internet browser Navigate to: http:<IP Address>

<IP address>: IP address of the PremierWave XN device

Default login credentials: admin, PASS

- 4. Click on System tab on the left.
- Click on Upload New Firmware and choose 'premierwave_xn_7_9_0_0RXX_python.rom' or

'premierwave_xn_7_9_0_0RXX+python.rom' (saved in step 1).

6. Click Upload.

The device will automatically reboot after firmware has been updated.

Firmware upgrade from 7.3 to 7.9:

C. Using Lantronix Device Installer

To use the DeviceInstaller utility, first install the latest version of the DeviceInstaller from the downloads page on the

Lantronix web site <u>www.lantronix.com/downloads</u>.

Run the executable to start the installation process and follow the installation wizard prompts. (If prompted to select an installation type, select Typical.)

Install base version of 7.9.0.0 firmware

- 1. Take the backup of existing device configuration (with export secrets options selected). This can be done via the Web Manger or by using the CLI. Please refer to the user guide for detailed steps.
- 2. Connect to the PW XN using serial port.
- 3. Start the DeviceInstaller program. Click Start -> All Programs -> Lantronix -> DeviceInstaller 4.4 -> DeviceInstaller.
- 4. Click Tools -> Recover Firmware
- 5. Choose the correct COM port to which the PWXN is connected.
- 6. Select Device Model: PremierWave XN P2
- 7. Check 'Erase All Flash'
- 8. Select Firmware file:premierwave_xn_7_9_0_0R19+python.rom and click OK.
- 9. Follow on screen instructions to complete the serial recovery and device reboot.
- 10. Restore the device configuration by importing the backup XML file saved in step 2. This can be done via the Web Manger or by using the CLI. Please refer to the user guide for detailed steps.